(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 31 December 2003 (31.12.2003)

PCT

English

(10) International Publication Number WO 2004/001605 A1

(51) International Patent Classification7: G06F 12/02, 3/06

OX Basyonotsuji Building, 3-16, Ichiban-cho, 3-chome, Aoba-Ku, Sendai-Shi, Miyagi 980-0811 (JP).

(74) Agent: KIMURA, Mitsuru; 2nd Floor, Kyohan Build-

ing, 7, Kandanishiki-cho 2-chome, Chiyoda-ku, Tokyo

(21) International Application Number:

PCT/JP2003/007672

17 June 2003 (17.06.2003) (22) International Filing Date:

English

(26) Publication Language:

(30) Priority Data: 2002-178674 19 June 2002 (19.06.2002) (81) Designated State (national): US.

101-0054 (JP).

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (for all designated States except US): TOKYO ELECTRON DEVICE LIMITED [JP/JP]; 1, Higashikata-cho, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-0045 (JP).

Published:

- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments


(72) Inventor; and

(25) Filing Language:

(75) Inventor/Applicant (for US only): KIKUCHI, Syuichi [JP/JP]; c/o TOKYO ELECTRON DEVICE LIMITED,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MEMORY DEVICE, MEMORY MANAGING METHOD AND PROGRAM



(57) Abstract: Disclosed is a memory device which is not easily deteriorated and a memory managing method which does not easily deteriorate a memory device. A physical address is given to a memory area of a flash memory (11) page by page. When supplied with to-bewritten data and a logical address where the data is to be written, a CPU (121) writes this data in a page indicated by a write pointer. The correlation between the physical address and the logical address of the page is stored in a RAM (123) in the form of BPT (Block Pointer Table). At the time of reading, the CPU (121) that has been supplied with the logical address searches the BPT to specify a physical address associated with that logical address and reads data from that page which is given the specified physical address. Flash erasing of a block is executed when the number of empty blocks becomes equal to or smaller than a predetermined number.